



INDOOR CCTV CAMERAS

Indoor cameras fit in any corner of your room and provide seamless monitoring from your smartphone and screen monitor



Our Wi-Fi security cameras connect to your home wireless network in minutes and record to an microSD card. With App access with motion detection alerts

WIFI 4 CH NVR KIT - 2MP CAMERAS- 12.5 INCH SCREEN - 1TB HARD-DISK

- 4 WiFi Cameras
- 12.5 Screen NVR
- 1TB Hard-disk

[Read More](#)

Price: ~~KSh39,999.00~~ KSh44,999.00 Excl VAT

Our PoE Surveillance Cameras save on hardware costs and installation time by delivering both power and data over a single Ethernet cable

UNIVIEW IPC322LR3 2MP VANDAL-RESISTANT NETWORK IR FIXED DOME CAMERA

- IP camera
- Easy range
- 1/2.7" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- 2.8 mm Lens
- 0 Lux - IR Range 30 m
- Compression Ultra265/H.265/H.264
- RJ-45 10/100 BaseT
- PoE IEEE802.3af
- Weatherproof IP67
- Vandal proof IK10
- IR Cut
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible



[Read More](#)

Price: KSh5,000.00 ~~KSh5,900.00~~ Excl VAT



FOSCAM R2M 1080P 2MP - PTZ WI-FI CAMERA - AUDIO - SD CARD RECORDING

- High Definition 1080p video
- Pan/Tilt Operation
- 350-degree pan / 100 degree tilt
- H.264 video compression
- Push alerts to iOS or Android on audio or motion
- 2 way audio with built-in speaker and microphone
- 26 foot (8 meters) IR range
- WIFI and wired Ethernet connectivity
- Free cloud service
- Flexible storage options, microSD (Up to 128 GB), cloud or NVR

[Read More](#)

Price: KSh5,999.00 ~~KSh7,999.00~~ Excl VAT

Indoor cameras fit in any corner of your room and provide seamless monitoring from your smartphone and screen monitor

FOSCAM C2M 1080P 2MP WI-FI CAMERA - AUDIO - SD CARD RECORDING

- Simple Setup
- 2.4/5GHz WiFi
- Plug&Play (EZlink)
- Human detection
- Alexa support
- High image & video quality with H264 & 2 Megapixel
- Auto IR
- Night visibility up to 8 meters
- Allows remote viewing & recording from anywhere at anytime
- 103° viewing angle
- SD Card Slot

[Read More](#)

Price: KSh5,999.00 Excl VAT



FOSCAM FI9826P WIRELESS INDOOR 960P 1.3MP HD IP CAMERA

- 1.3 Megapixel HD Pan/Tilt/Zoom Wired/Wireless IP Camera
- 3x Zoom Lens with detailed view
- WPS enabled wireless connectivity (Wi-Fi)
- Supports two-way audio, built-in mic and speaker
- H.264 video compression
- Free Foscam DDNS Service Embedded
- Motion detection alarm via E-mail and FTP
- Plug-and-play Installation
- Free Foscam iOS and Android app
- Supports Micro SD card

[Read More](#)

Price: ~~KSh4,999.00~~ ~~KSh5,999.00~~ Excl VAT



FOSCAM FI9821P WIRELESS INDOOR 720P HD PAN/TILT IP CAMERA

- 1.0 MegaPixel High Definition (1280 x 720)
- WPS-enabled Wireless Connection
- Video Recording On Motion Detection
- Night Surveillance Up To 8 Meters
- Embedded IR-Cut Improves Image Clarity
- Wide Viewing Angle - 70 Degrees
- Pan & Tilt - 300° Horizontal, 120° Vertical
- Free Embedded Foscam DDNS Server
- Micro SD Card Slot (Up to 32GB)

[Read More](#)

Price: ~~KSh4,999.00~~ ~~KSh5,999.00~~ Excl VAT





NETWORK VIDEO RECORDERS (NVR)

NVR Recorders for CCTV systems are available in 9, 16 and 32 channels for IP CCTV Security Cameras monitoring and recording.

NVR Recorders for CCTV systems are available in 9, 16 and 32 channels for IP CCTV Security Cameras monitoring and recording.

NVR302-S-P SERIES 8/16 CHANNEL 2 HDDS NVR



Model	NVR302-08S-P8	NVR302-16S-P8	NVR302-16S-P16
Video/Audio Input			
IP Video Input	8-ch	16-ch	16-ch
Two-way Audio Input	1-ch, RCA		
Network			
Incoming Bandwidth	160Mbps		
Outgoing Bandwidth	96Mbps	96Mbps	96Mbps
Remote Users	128		
Protocols	P2P, UPnP, NTP, DHCP, PPPoE		
Video/Audio Output			

HDMI/VGA Output	VGA: 1024X768@60, 1280X720@60, 1280X1024@60, 1920X1080@50, 1920X1080@60		
	HDMI: 4k (3840x2160@30), 4k (3840x2160@60), 1024X768@60, 1280X720@60, 1280X1024@60, 1920X1080@50, 1920X1080@60		
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF		
Audio Output	1-ch, RCA		
Synchronous Playback	8-ch	16-ch	16-ch
Corridor Mode Screen	3/4/5/7/9	3/4/5/7/9/10/12/1 6	3/4/5/7/9/10/12/1 6
Decoding			
Decoding format	Ultra265/H.265/H.264		
Live view/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF		
Capability	1 x 4K@30, 2 x 4MP@3 0, 3 x 1 x 4K@30, 2 x 4MP@30, 3 x 3MP@25, 4 x 5, 4 x 1080P@30, 8 x 1080P@ 720P@30,16 x D1 30, 8 x 720P@3 0,16 x D1		
	1 x 4K@30, 2 x 4MP@30, 3 x 3MP@25, 4 x 1080P@30, 8 x 720P@30		
Hard Disk			
SATA	2 SATA interfaces		
Capacity	up to 10TB for each disk		
External Interface			
Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface		
USB Interface	Front panel: 1 x USB2.0, Rear panel: 1 x USB2.0		
Alarm In	4-ch		
Alarm Out	1-ch		
PoE			
Interface	8 RJ-45 10M/100M self-adaptive Ethernet Interface		16 RJ-45 10M/100M self- adaptive Ethernet Interface
Max Power	Max 30W for single port Max 130W in total	Max 30W for single port Max 130W in total	Max 30W for single port Max 240W in total

Supported Standard	IEEE 802.3af/at
General	
Power Supply	220V AC Power Consumption: ≤9 W (without HDD)
Working Environment	-10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing)
Dimensions (W×D×H)	380mm ×315mm × 53mm (15.0" × 12.4" ×2.1")
Weight (without HDD)	≤2.4kg (5.29lb)

Copyright 2011-202

[Read More](#)

Price: ~~KSh24,000.00~~ ~~KSh25,000.00~~ Excl VAT

NVR Recorders for CCTV systems are available in 9, 16 and 32 channels for IP CCTV Security Cameras monitoring and recording.

NVR302-32S 32 CHANNEL 2 HDD NVR



Model NVR302-32S

Video/Audio Input

IP Video Input 32-ch

Two-way Audio Input 1-ch, RCA

Network

Incoming bandwidth 160Mbps

Outgoing bandwidth 64Mbps

Remote Users 128

Protocols P2P, UPnP, NTP, DHCP, PPPoE

Video/Audio Output

HDMI:

4K (3840x2160) @30, 1920x1080p@60,
1920x1080p@50, 1600x1200@60, 1280x1024@60,
1280x720@60, 1024x768@60

HDMI/VGA Output

VGA:

1920x1080p@60, 1920x1080p@50, 1280x1024@60,
1280x720@60, 1024x768@60

Audio Output 1-ch, RCA

Recording Resolution 8MP/5MP/4MP/3MP/1080p/960p/720p/960H/D1/2CIF/
CIF

Synchronous Playback 32-ch

Corridor Mode Screen 3/4/5/7/9/10/12/16/32

Decoding	
Decoding format	Ultra265/H.265/H.264
Live view/Playback	8MP/5MP/4MP/3MP/1080p/960p/960H/720p/D1/2CIF/ CIF
Capability	2 x 4K@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30, 8 x 1080p@30, 16 x 720p@30,32 x D1
Hard Disk	
SATA	2 SATA interfaces
Capacity	up to 6TB for each disk
External Interface	
Network Interface	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interfaces
USB Interface	Rear panel: 1 x USB2.0, 1 x USB3.0 Front panel: 1 x USB2.0
General	
Power Supply	12V DC Power Consumption: ≤ 15W(without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing)
Dimensions (W×D×H)	380mm × 315mm ×53mm (15.0" × 12.4" ×2.1")
Weight (without HDD)	≤ 2.48 Kg (5.47 lb)

[Read More](#)
Price: ~~KSh24,000.00~~ ~~KSh26,000.00~~ Excl VAT

NVR Recorders for CCTV systems are available in 9, 16 and 32 channels for IP CCTV Security Cameras monitoring and recording.

NVR201-04LP NETWORK VIDEO RECORDER



Model	NVR201-04U	NVR201-08Q
Video/Audio Input		
Analog Video Input	4-ch, BNC	8-ch, BNC
IP Video Input	2-ch (only IP up to 6ch)	2-ch (only IP up to 10ch)

Supported Analog Camera Types	Support AHD input:	Support AHD input:
	5MP, 4MP, 3MP, 1080P/30 Hz□1080P/25 Hz, 720P/30 Hz,720P/25 Hz,	3MP,1080P/30 Hz, 1080P/25 Hz□720P/25 Hz, 720P/30 Hz
	Support TVI input:	Support TVI input:
	5MP,3MP,1080P/30 Hz, 1080P/25 Hz, 720P/30 Hz,720P/25 Hz	3MP,1080P/30 Hz, 1080P/25 Hz 720P/25 Hz,720P/30 Hz
	Support CVI input:	Support CVI input:
Audio Input	1080P/25Hz, 1080P/30Hz, 720P/25Hz,720P/30Hz	1080P/25Hz, 1080P/30Hz, 720P/25Hz,720P/30Hz
	Support CVBS input	Support CVBS input
	4-ch, RCA	
Two-way Audio Input	1-ch, RCA	
Read More		
Price: KSh10,000.00 KSh12,000.00 Excl VAT		

NVR Recorders for CCTV systems are available in 9, 16 and 32 channels for IP CCTV Security Cameras monitoring and recording.

NVR301-08X-P8 8 CHANNEL 1 HDD NVR

Model	NVR301-08X-P8
Video/Audio Input	
IP Video Input	8-ch
Two-way Audio Input	1-ch, RCA
Network	
Incoming Bandwidth	80Mbps
Outgoing Bandwidth	64Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	



HDMI/VGA Output	HDMI: 3840x2160/30Hz,1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
	VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Recording Resolution	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, RCA
Synchronous Playback	8-ch
Corridor Mode Screen	3/4/5/7/9
Decoding	
Decoding format	Ultra 265/H.265/H.264
Liveview/Playback	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	2 x 4k@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30,8 x 1080p@30
Hard Disk	
SATA	1 SATA interface
Capacity	up to 6TB for each disk
External Interface	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 1 x USB2.0,1 x USB3.0
PoE	
Interface	8 RJ45 10M/100M self-adaptive Ethernet Interface
Max Power	Max 30W for single port Max 75W in total
Supported Standard	IEEE 802.3at, IEEE 802.3af
General	
Power Supply	52V DC Power Consumption: ≤8 W (without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing)
Dimensions (WxDxH)	260mm × 240mm × 47mm (10.2"×9.4"×1.9 ")

Weight (without HDD) 1kg (2.20 lb)

[Read More](#)

Price: ~~KSh13,000.00~~ KSh15,000.00 Excl VAT

FOSCAM FN3109H 9CH NVR - NETWORK VIDEO RECORDER



- 9 channels HD IP Camera access
- H.264 Main Profile video compression
- Supports HDMI and VGA local display
- 4-ch Video Synchronous Playback
- Compatible with Foscam HD and MJPEG cameras
- Supports ONVIF protocol
- Supports USB External storage (Flashdisk,HDD)

[Read More](#)

Price: ~~KSh9,999.00~~ KSh15,999.00 Excl VAT



OUTDOOR CCTV CAMERAS

WiFi and PoE CCTV Cameras for outdoor use in home and business including bullet and PTZ dome cameras. Buy online today with 1-year guarantee and technical support



Our Wi-Fi security cameras connect to your home wireless network in minutes and record to an microSD card. With App access with motion detection alerts

WIFI 4 CH NVR KIT - 2MP CAMERAS- 12.5 INCH SCREEN - 1TB HARD-DISK

- 4 WiFi Cameras
- 12.5 Screen NVR
- 1TB Hard-disk

[Read More](#)

Price: ~~KSh39,999.00~~ KSh44,999.00 Excl VAT

WiFi and PoE CCTV Cameras for outdoor use in home and business including bullet and PTZ dome cameras. Buy online today with 1-year guarantee and technical support

UNIVIEW IPC325LR3 5MP VANDAL-RESISTANT NETWORK IR FIXED DOME CAMERA

	IPC325LR3-VSPF28-D			IPC325LR3-VSPF40-D	
Camera					
Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS				
Lens	2.8mm@F2.0		4.0mm@F2.0		
	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
DORI					
Distance	2.8	42	16.8	8.4	4.2
	4.0	60	24	12	6
Angle of View (H)	105.3°		79.7°		
Angle of View (V)	69.5°		51.8°		
Angle of View (O)	136.9°		98.0°		
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 75°		
Shutter	Auto/Manual, 1 ~ 1/100000s				
Minimum Illumination	Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	>52dB				
IR Range	Up to 30m (98ft) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	DWDR				
Video					
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile				



Frame Rate	Main Stream: 5MP (2592*1944), Max 20fps; Sub Stream: 720P (1280*720), Max 20fps
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°
Dewarping	NA
HLC	Supported
BLC	Supported
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Compatible Integration	ONVIF (Profile S, Profile T), API
Client	EZStation EZView EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	
Network	10M/100M Base-TX Ethernet
Certifications	
	CE: EN 60950-1
Certifications	UL: UL60950-1
	FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 4W

Dimensions (Ø x H)	Φ109 x 81mm (Ø4.3" x 3.2")
Net Weight	0.45kg (0.99lb)
Material	Metal + Plastic
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Ingress Protection	IP67
Vandal Resistant	IK10

[Read More](#)

Price: ~~KSh8,000.00~~ KSh9,000.00 Excl VAT



Our PoE Surveillance Cameras save on hardware costs and installation time by delivering both power and data over a single Ethernet cable

UNIVIEW IPC2124LR3 4MP MINI FIXED BULLET NETWORK CAMERA

	IPC2124LR3-PF40M-D		IPC2124LR3-PF60M-D		
Camera					
Sensor	1/3", 4.0 megapixel, progressive scan, CMOS				
Lens	4.0mm@F2.0		6.0mm@F2.0		
	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
DORI Distance	4.0	90	36	18	9
	6.0	135	54	27	13.5
Angle of View (H)	78.9°		49.9°		
Angle of View (V)	39.6°		27.0°		
Angle of View (O)	97.0°		57.7°		
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 90°		Rotate: 0° ~ 360°
Shutter	Auto/Manual, 1 ~ 1/100000s				

Minimum Illumination	Colour: 0.03Lux (F2.0, AGC ON) 0Lux with IR on
Digital noise reduction	2D/3D DNR
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52dB
IR Range	Up to 30m (98ft) IR range
Wavelength	850nm
IR On/Off Control	Auto/Manual
Defog	Digital Defog
WDR	DWDR
Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile
Frame Rate	Main Stream: 4MP (2592*1520), Max 20fps; Sub Stream: 720P (1280*720), Max 20fps; Third Stream: D1 (720*576), Max 20fps
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°
Dewarping	NA
HLC	Supported
BLC	Supported
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Compatible Integration	ONVIF (Profile S, Profile T), API
Client	EZStation EZView EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	

Network	10/100M Base-TX Ethernet
Certifications	CE: EN 60950-1
Certifications	UL: UL60950-1
Certifications	FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 5W
Dimensions (L × W × H)	167.3 × 62.9 × 62.7mm (6.6" × 2.5" × 2.5")
Net Weight	0.45kg (0.99lb)
Material	Metal
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Ingress Protection	IP67
Reset Button	Supported

[Read More](#)

Price: ~~KSh7,000.00~~ ~~KSh8,000.00~~ Excl VAT

Our PoE Surveillance Cameras save on hardware costs and installation time by delivering both power and data over a single Ethernet cable

UNIVIEW IPC322LR3 2MP VANDAL-RESISTANT NETWORK IR FIXED DOME CAMERA



- IP camera
- Easy range
- 1/2.7" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- 2.8 mm Lens
- 0 Lux - IR Range 30 m
- Compression Ultra265/H.265/H.264
- RJ-45 10/100 BaseT
- PoE IEEE802.3af
- Weatherproof IP67
- Vandal proof IK10
- IR Cut
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

[Read More](#)

Price: ~~KSh5,000.00~~ KSh5,900.00 Excl VAT



Our PoE Surveillance Cameras save on hardware costs and installation time by delivering both power and data over a single Ethernet cable

UNIVIEW IPC2122LR3 2MP MINIFIXED BULLET NETWORK CAMERA

	IPC2122LR3-PF40M-D		IPC2122LR3-PF60M-D		
Camera					
Sensor	1/2.7", 2.0 megapixel, progressive scan, CMOS				
Lens	4.0mm@F2.0		6.0mm@F2.0		
	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
DORI					
Distance	4.0	66.7	26.7	13.3	6.7
	6.0	90	36	18	9
Angle of View (H)	86.5°		55.4°		
Angle of View (V)	44.1°		30.2°		
Angle of View (O)	106.4°		68.1°		
Adjustment angle	Pan: 0° ~ 360° Tilt: 0° ~ 90°			Rotate: 0° ~ 360°	
Shutter	Auto/Manual, 1 ~ 1/100000s				
Minimum Illumination	Colour: 0.02Lux (F2.0, AGC ON) 0Lux with IR on				
Digital noise reduction	2D/3D DNR				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>52dB				
IR Range	Up to 30m (98ft) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	DWDR				
Video					
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile				

	Main Stream: 1080P (1920*1080), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; Third Stream: CIF (352*288), Max 30fps
Frame Rate	
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
Privacy Mask	Up to 8 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°
Dewarping	Supported
HLC	Supported
BLC	Supported
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Compatible Integration	ONVIF (Profile S, Profile T), API
Client	EZStation EZView EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	
Network	10/100M Base-TX Ethernet
Certifications	
Certifications	CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 4.5W
Dimensions (L × W × H)	167.3 × 62.9 × 62.7mm (6.6" × 2.5" × 2.5")
Net Weight	0.45kg (0.99lb)
Material	Metal
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)

Surge Protection	2KV
Ingress Protection	IP67
Reset Button	Supported

[Read More](#)

Price: ~~KSh5,000.00~~ ~~KSh6,000.00~~ Excl VAT

Our Wi-Fi security cameras connect to your home wireless network in minutes and record to an microSD card. With App access with motion detection alerts

WIFI 2MP 1080P 7W SOLAR CAMERA WITH AUDIO - WEATHERPROOF

- 2mp and 1080p full HD
- Support PIR human infrared detection
- Low-consumption
- Wire-free
- Audio in and audio out.

[Read More](#)

Price: ~~KSh9,999.00~~ ~~KSh10,999.00~~ Excl VAT





FOSCAM FI9902P 1080P 2MP - BULLET WI-FI CAMERA - SD CARD RECORDING

- 1080p video resolution at 25 frames per second, powered by a smart chipset
- Remote viewing and recording from anywhere, anytime
- Intelligent real-time push alerts with AI human detection
- Works with Alexa - View camera with voice control
- Wide viewing angle: Horizontal 89°, Diagonal 105°
- 6x Digital Zoom
- Night vision range up to 20 metres (66ft)
- Multiple storage methods including an external access SD slot

[Read More](#)

Price: ~~KSh6,999.00~~ ~~KSh9,999.00~~ Excl VAT

FOSCAM FI9828P WIRELESS IP OUTDOOR PTZ CAMERA

- 1.3 Megapixel HD IP Camera
- Waterproof
- H.264 video kompression and Mjpeg-stream
- Day/Night mode
- IR LEDs On/Off manually and automatically
- Nightvision up to 20 m
- Angle 70 maximum (slewing of 355 horizontal, slewing of 90 vertical)
- 2 way audio support
- Motion control via E-Mail and FTP
- Free DDNS-Service
- Minimum light intensity 0 Lux
- Power consumption

[Read More](#)

Price: ~~KSh15,999.00~~ ~~KSh19,999.00~~ Excl VAT





POE CAMERAS

Our PoE Surveillance Cameras save on hardware costs and installation time by delivering both power and data over a single Ethernet cable



WiFi and PoE CCTV Cameras for outdoor use in home and business including bullet and PTZ dome cameras. Buy online today with 1-year guarantee and technical support

UNIVIEW IPC325LR3 5MP VANDAL-RESISTANT NETWORK IR FIXED DOME CAMERA

	IPC325LR3-VSPF28-D			IPC325LR3-VSPF40-D	
Camera					
Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS				
Lens	2.8mm@F2.0		4.0mm@F2.0		
	Lens (mm)	Detect (m)	Observe (m)	Recogni ze (m)	Identify (m)
DORI					
Distance	2.8	42	16.8	8.4	4.2
	4.0	60	24	12	6
Angle of View (H)	105.3°		79.7°		
Angle of View (V)	69.5°		51.8°		
Angle of View (O)	136.9°		98.0°		

Adjustment angle	Pan: 0° ~ 360°	Tilt: 0° ~ 75°
Shutter	Auto/Manual, 1 ~ 1/100000s	
Minimum Illumination	Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR	
Day/Night	IR-cut filter with auto switch (ICR)	
Digital noise reduction	2D/3D DNR	
S/N	>52dB	
IR Range	Up to 30m (98ft) IR range	
Wavelength	850nm	
IR On/Off Control	Auto/Manual	
Defog	Digital Defog	
WDR	DWDR	
Video		
Video Compression	Ultra 265, H.265, H.264, MJPEG	
H.264 code profile	Baseline profile, Main Profile	
Frame Rate	Main Stream: 5MP (2592*1944), Max 20fps; Sub Stream:720P (1280*720), Max 20fps	
Video Bit Rate	128 Kbps~16 Mbps	
OSD	Up to 4 OSDs	
Privacy Mask	Up to 4 areas	
ROI	Up to 2 areas	
Motion Detection	Up to 4 areas	
Image		
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2	
Digital noise reduction	2D/3D DNR	
Smart IR	Support	
Flip	Normal/Vertical/Horizontal/180°	
Dewarping	NA	
HLC	Supported	
BLC	Supported	
Network		

Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Compatible Integration	ONVIF (Profile S, Profile T), API
Client	EZStation EZView EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chorme 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	
Network	10M/100M Base-TX Ethernet
Certifications	
	CE: EN 60950-1
Certifications	UL: UL60950-1
	FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 4W
Dimensions (Ø x H)	Ø109 x 81mm (Ø4.3" x 3.2")
Net Weight	0.45kg (0.99lb)
Material	Metal + Plastic
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Ingress Protection	IP67
Vandal Resistant	IK10

[Read More](#)

Price: KSh8,000.00 ~~KSh9,000.00~~ Excl VAT

Our PoE Surveillance Cameras save on hardware costs and installation time by delivering both power and data over a single Ethernet cable

UNIVIEW IPC2124LR3 4MP MINI FIXED BULLET NETWORK CAMERA

	IPC2124LR3-PF40M-D		IPC2124LR3-PF60M-D		
Camera					
Sensor	1/3", 4.0 megapixel, progressive scan, CMOS				
Lens	4.0mm@F2.0		6.0mm@F2.0		
DORI Distance	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
	4.0	90	36	18	9
	6.0	135	54	27	13.5
Angle of View (H)	78.9°		49.9°		
Angle of View (V)	39.6°		27.0°		
Angle of View (O)	97.0°		57.7°		
Adjustment angle	Pan: 0° ~ 360° Tilt: 0° ~ 90°		Rotate: 0° ~ 360°		
Shutter	Auto/Manual, 1 ~ 1/100000s				
Minimum Illumination	Colour: 0.03Lux (F2.0, AGC ON) 0Lux with IR on				
Digital noise reduction	2D/3D DNR				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>52dB				
IR Range	Up to 30m (98ft) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	DWDR				
Video					
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile				
Frame Rate	Main Stream: 4MP (2592*1520), Max 20fps; Sub Stream: 720P (1280*720), Max 20fps; Third Stream: D1 (720*576), Max 20fps				
Video Bit Rate	128 Kbps~16 Mbps				
OSD	Up to 4 OSDs				
Privacy Mask	Up to 4 areas				
ROI	Up to 2 areas				



Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°
Dewarping	NA
HLC	Supported
BLC	Supported
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Compatible Integration	ONVIF (Profile S, Profile T), API
Client	EZStation EZView EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chorme 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	
Network	10/100M Base-TX Ethernet
Certifications	
Certifications	CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 5W
Dimensions (L × W × H)	167.3 × 62.9 × 62.7mm (6.6" × 2.5" × 2.5")
Net Weight	0.45kg (0.99lb)
Material	Metal
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Ingress Protection	IP67
Reset Button	Supported

[Read More](#)

Price: ~~KSh7,000.00~~ ~~KSh8,000.00~~ Excl VAT



Our PoE Surveillance Cameras save on hardware costs and installation time by delivering both power and data over a single Ethernet cable

UNIVIEW IPC322LR3 2MP VANDAL-RESISTANT NETWORK IR FIXED DOME CAMERA

- IP camera
- Easy range
- 1/2.7" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- 2.8 mm Lens
- 0 Lux - IR Range 30 m
- Compression Ultra265/H.265/H.264
- RJ-45 10/100 BaseT
- PoE IEEE802.3af
- Weatherproof IP67
- Vandal proof IK10
- IR Cut
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible

[Read More](#)
Price: KSh5,000.00 ~~KSh5,900.00~~ Excl VAT

Our PoE Surveillance Cameras save on hardware costs and installation time by delivering both power and data over a single Ethernet cable

UNIVIEW IPC2122LR3 2MP MINIFIXED BULLET NETWORK CAMERA

	IPC2122LR3-PF40M-D		IPC2122LR3-PF60M-D		
Camera					
Sensor	1/2.7", 2.0 megapixel, progressive scan, CMOS				
Lens	4.0mm@F2.0		6.0mm@F2.0		
	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
DORI					
Distance	4.0	66.7	26.7	13.3	6.7
	6.0	90	36	18	9
Angle of View (H)	86.5°		55.4°		
Angle of View (V)	44.1°		30.2°		



Angle of View (O)	106.4°	68.1°
Adjustment angle	Pan: 0° ~ 360° Tilt: 0° ~ 90°	Rotate: 0° ~ 360°
Shutter	Auto/Manual, 1 ~ 1/100000s	
Minimum Illumination	Colour: 0.02Lux (F2.0, AGC ON) 0Lux with IR on	
Digital noise reduction	2D/3D DNR	
Day/Night	IR-cut filter with auto switch (ICR)	
S/N	>52dB	
IR Range	Up to 30m (98ft) IR range	
Wavelength	850nm	
IR On/Off Control	Auto/Manual	
Defog	Digital Defog	
WDR	DWDR	
Video		
Video Compression	Ultra 265, H.265, H.264, MJPEG	
H.264 code profile	Baseline profile, Main Profile	
Frame Rate	Main Stream: 1080P (1920*1080), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; Third Stream: CIF (352*288), Max 30fps	
Video Bit Rate	128 Kbps~16 Mbps	
OSD	Up to 4 OSDs	
Privacy Mask	Up to 8 areas	
ROI	Up to 2 areas	
Motion Detection	Up to 4 areas	
Image		
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2	
Digital noise reduction	2D/3D DNR	
Smart IR	Support	
Flip	Normal/Vertical/Horizontal/180°	
Dewarping	Supported	
HLC	Supported	
BLC	Supported	
Network		
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS	
Compatible Integration	ONVIF (Profile S, Profile T), API	

Client	EZStation
	EZView
	EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below
	Plug-in free live view: Chorme 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	
Network	10/100M Base-TX Ethernet
Certifications	
Certifications	CE: EN 60950-1
	UL: UL60950-1
	FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 4.5W
Dimensions (L × W × H)	167.3 × 62.9 × 62.7mm (6.6" × 2.5" × 2.5")
Net Weight	0.45kg (0.99lb)
Material	Metal
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Ingress Protection	IP67
Reset Button	Supported

[Read More](#)

Price: ~~KSh5,000.00~~ ~~KSh6,000.00~~ Excl VAT



WIFI CAMERAS

Our Wi-Fi security cameras connect to your home wireless network in minutes and record to an microSD card. With App access with motion detection alerts



Our Wi-Fi security cameras connect to your home wireless network in minutes and record to an microSD card. With App access with motion detection alerts

TUYA 4G SOLAR FLOODLIGHT PTZ CAMERA

- 4G Simcard support.
- Tuya Mobile App.
- PIR Human Body Induction Detection, Remote Push Alarm Information
- Two-way Voice Built-in Microphone And Speaker
- Waterproof IP66, Install Anywhere You Want
- High-definition Night Vision Infrared Night Vision Up To 30M (Color Full Night Vision)
- Support Cloud Storage And Local SD Card Storage
- Support 6 Batteries, Ultra-Low Power Solar Charging,
- 5M Extension Cable Can Be Installed Separately.

[Read More](#)

Price: ~~KSh19,999.00~~ KSh21,999.00 Excl VAT

Our Wi-Fi security cameras connect to your home wireless network in minutes and record to an microSD card. With App access with motion detection alerts

TUYA WIFI 3MP FLOODLIGHT PTZ CAMERA

- 3MP & 1080P FHD
- Color Night Vision
- Motion Tracking
- Two ways audio
- SD Card record upto 128GB
- Tuya mobile App monitoring.

[Read More](#)

Price: ~~KSh9,999.00~~ KSh10,999.00 Excl VAT



Our Wi-Fi security cameras connect to your home wireless network in minutes and record to an microSD card. With App access with motion detection alerts

WIFI 4 CH NVR KIT - 2MP CAMERAS- 12.5 INCH SCREEN - 1TB HARD-DISK

- 4 WiFi Cameras
- 12.5 Screen NVR
- 1TB Hard-disk

[Read More](#)

Price: ~~KSh39,999.00~~ KSh44,999.00 Excl VAT

Our Wi-Fi security cameras connect to your home wireless network in minutes and record to an microSD card. With App access with motion detection alerts

WIFI 2MP 1080P 7W SOLAR CAMERA WITH AUDIO - WEATHERPROOF

- 2mp and 1080p full HD
- Support PIR human infrared detection
- Low-consumption
- Wire-free
- Audio in and audio out.

[Read More](#)

Price: ~~KSh9,999.00~~ ~~KSh10,999.00~~ Excl VAT



FOSCAM R2M 1080P 2MP - PTZ WI-FI CAMERA - AUDIO - SD CARD RECORDING

- High Definition 1080p video
- Pan/Tilt Operation
- 350-degree pan / 100 degree tilt
- H.264 video compression
- Push alerts to iOS or Android on audio or motion
- 2 way audio with built-in speaker and microphone
- 26 foot (8 meters) IR range
- WIFI and wired Ethernet connectivity
- Free cloud service
- Flexible storage options, microSD (Up to 128 GB), cloud or NVR

[Read More](#)

Price: ~~KSh5,999.00~~ ~~KSh7,999.00~~ Excl VAT

FOSCAM FI9902P 1080P 2MP - BULLET WI-FI CAMERA - SD CARD RECORDING

- 1080p video resolution at 25 frames per second, powered by a smart chipset
- Remote viewing and recording from anywhere, anytime
- Intelligent real-time push alerts with AI human detection
- Works with Alexa - View camera with voice control
- Wide viewing angle: Horizontal 89°, Diagonal 105°
- 6x Digital Zoom
- Night vision range up to 20 metres (66ft)
- Multiple storage methods including an external access SD slot



[Read More](#)

Price: ~~KSh6,999.00~~ ~~KSh9,999.00~~ Excl VAT



Indoor cameras fit in any corner of your room and provide seamless monitoring from your smartphone and screen monitor

FOSCAM C2M 1080P 2MP WI-FI CAMERA - AUDIO - SD CARD RECORDING

- Simple Setup
- 2.4/5GHz WiFi
- Plug&Play (EZlink)
- Human detection
- Alexa support
- High image & video quality with H264 & 2 Megapixel
- Auto IR
- Night visibility up to 8 meters
- Allows remote viewing & recording from anywhere at anytime
- 103° viewing angle
- SD Card Slot

[Read More](#)

Price: KSh5,999.00 Excl VAT

FOSCAM FI9828P WIRELESS IP OUTDOOR PTZ CAMERA

- 1.3 Megapixel HD IP Camera
- Waterproof
- H.264 video kompression and Mjpeg-stream
- Day/Night mode
- IR LEDs On/Off manually and automatically
- Nightvision up to 20 m
- Angle 70 maximum (slewing of 355 horizontal, slewing of 90 vertical)
- 2 way audio support
- Motion control via E-Mail and FTP
- Free DDNS-Service
- Minimum light intensity 0 Lux
- Power consumption

[Read More](#)

Price: KSh15,999.00 ~~KSh19,999.00~~ Excl VAT



FOSCAM FI9826P WIRELESS INDOOR 960P 1.3MP HD IP CAMERA

- 1.3 Megapixel HD Pan/Tilt/Zoom Wired/Wireless IP Camera
- 3x Zoom Lens with detailed view
- WPS enabled wireless connectivity (Wi-Fi)
- Supports two-way audio, built-in mic and speaker
- H.264 video compression
- Free Foscam DDNS Service Embedded
- Motion detection alarm via E-mail and FTP
- Plug-and-play Installation
- Free Foscam iOS and Android app
- Supports Micro SD card

[Read More](#)

Price: KSh4,999.00 ~~KSh5,999.00~~ Excl VAT



FOSCAM FI9821P WIRELESS INDOOR 720P HD PAN/TILT IP CAMERA

- 1.0 MegaPixel High Definition (1280 x 720)
- WPS-enabled Wireless Connection
- Video Recording On Motion Detection
- Night Surveillance Up To 8 Meters
- Embedded IR-Cut Improves Image Clarity
- Wide Viewing Angle - 70 Degrees
- Pan & Tilt - 300° Horizontal, 120° Vertical
- Free Embedded Foscam DDNS Server
- Micro SD Card Slot (Up to 32GB)

[Read More](#)

Price: ~~KSh4,999.00~~ ~~KSh5,999.00~~ Excl VAT

