



NETWORK VIDEO RECORDERS (NVR)

NVR Recorders for CCTV systems are available in 9, 16 and 32 channels for IP CCTV Security Cameras monitoring and recording.

NVR Recorders for CCTV systems are available in 9, 16 and 32 channels for IP CCTV Security Cameras monitoring and recording.



NVR302-S-P SERIES 8/16 CHANNEL 2 HDDS NVR

Model	NVR302-08S-P8	NVR302-16S-P8	NVR302-16S-P16
Video/Audio Input			
IP Video Input	8-ch	16-ch	16-ch
Two-way Audio Input	1-ch, RCA		
Network			
Incoming Bandwidth	160Mbps		
Outgoing Bandwidth	96Mbps	96Mbps	96Mbps
Remote Users	128		
Protocols	P2P, UPnP, NTP, DHCP, PPPoE		
Video/Audio Output			

HDMI/VGA Output	VGA: 1024X768@60, 1280X720@60, 1280X1024@60, 1920X1080@50, 1920X1080@60		
	HDMI: 4k (3840x2160@30), 4k (3840x2160@60), 1024X768@60, 1280X720@60, 1280X1024@60, 1920X1080@50, 1920X1080@60		
Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF		
Audio Output	1-ch, RCA		
Synchronous Playback	8-ch	16-ch	16-ch
Corridor Mode Screen	3/4/5/7/9	3/4/5/7/9/10/12/16	3/4/5/7/9/10/12/16
Decoding			
Decoding format	Ultra265/H.265/H.264		
Live view/Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF		
Capability	1 x 4K@30, 2 x 4MP@30, 1 x 4K@30, 2 x 4MP@30, 3 x 4MP@30, 3 x 3MP@25, 4 x 3MP@25, 4 x 1080P@30, 8 x 1080P@30, 8 x 720P@30		
	0, 3 x 1 x 4K@30, 2 x 4MP@30, 3 x 3MP@25, 4 x 1080P@30, 8 x 1080P@720P@30, 16 x D1 30, 8 x 720P@30, 16 x D1		
Hard Disk			
SATA	2 SATA interfaces		
Capacity	up to 10TB for each disk		
External Interface			
Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface		
USB Interface	Front panel: 1 x USB2.0, Rear panel: 1 x USB2.0		
Alarm In	4-ch		
Alarm Out	1-ch		
PoE			
Interface	8 RJ-45 10M/100M self-adaptive Ethernet Interface		16 RJ-45 10M/100M self-adaptive Ethernet Interface
Max Power	Max 30W for single port Max 130W in total	Max 30W for single port Max 130W in total	Max 30W for single port Max 240W in total

Supported Standard	IEEE 802.3af/at
General	
Power Supply	220V AC Power Consumption: ≤9 W (without HDD)
Working Environment	-10°C~+ 55°C (+14°F~+131°F), Humidity ≤ 90% RH (non-condensing)
Dimensions (W×D×H)	380mm ×315mm × 53mm (15.0" × 12.4" ×2.1")
Weight (without HDD)	≤2.4kg (5.29lb)

Copyright 2011-202

[Read More](#)

Price: ~~KSh24,000.00~~ ~~KSh25,000.00~~ Excl VAT

NVR Recorders for CCTV systems are available in 9, 16 and 32 channels for IP CCTV Security Cameras monitoring and recording.

NVR302-32S 32 CHANNEL 2 HDD NVR

Model	NVR302-32S
Video/Audio Input	
IP Video Input	32-ch
Two-way Audio Input	1-ch, RCA
Network	
Incoming bandwidth	160Mbps
Outgoing bandwidth	64Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	
HDMI/VGA Output	HDMI: 4K (3840x2160) @30, 1920x1080p@60, 1920x1080p@50, 1600x1200@60, 1280x1024@60, 1280x720@60, 1024x768@60 VGA: 1920x1080p@60, 1920x1080p@50, 1280x1024@60, 1280x720@60, 1024x768@60
Audio Output	1-ch, RCA
Recording Resolution	8MP/5MP/4MP/3MP/1080p/960p/720p/960H/D1/2CIF/ CIF
Synchronous Playback	32-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16/32



Decoding	
Decoding format	Ultra265/H.265/H.264
Live view/Playback	8MP/5MP/4MP/3MP/1080p/960p/960H/720p/D1/2CIF/ CIF
Capability	2 x 4K@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30, 8 x 1080p@30, 16 x 720p@30,32 x D1
Hard Disk	
SATA	2 SATA interfaces
Capacity	up to 6TB for each disk
External Interface	
Network Interface	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interfaces
USB Interface	Rear panel: 1 x USB2.0, 1 x USB3.0 Front panel: 1 x USB2.0
General	
Power Supply	12V DC Power Consumption: ≤ 15W(without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing)
Dimensions (W×D×H)	380mm × 315mm ×53mm (15.0" × 12.4" ×2.1")
Weight (without HDD)	≤ 2.48 Kg (5.47 lb)

[Read More](#)
Price: ~~KSh24,000.00~~ ~~KSh26,000.00~~ Excl VAT

NVR Recorders for CCTV systems are available in 9, 16 and 32 channels for IP CCTV Security Cameras monitoring and recording.

NVR201-04LP NETWORK VIDEO RECORDER



Model	NVR201-04U	NVR201-08Q
Video/Audio Input		
Analog Video Input	4-ch, BNC	8-ch, BNC
IP Video Input	2-ch (only IP up to 6ch)	2-ch (only IP up to 10ch)

Supported Analog Camera Types	Support AHD input:	Support AHD input:
	5MP, 4MP, 3MP, 1080P/30 Hz□1080P/25 Hz, 720P/30 Hz,720P/25 Hz,	3MP,1080P/30 Hz, 1080P/25 Hz□720P/25 Hz, 720P/30 Hz
	Support TVI input:	Support TVI input:
	5MP,3MP,1080P/30 Hz, 1080P/25 Hz, 720P/30 Hz,720P/25 Hz	3MP,1080P/30 Hz, 1080P/25 Hz 720P/25 Hz,720P/30 Hz
	Support CVI input:	Support CVI input:
Audio Input	1080P/25Hz, 1080P/30Hz, 720P/25Hz,720P/30Hz	1080P/25Hz, 1080P/30Hz, 720P/25Hz,720P/30Hz
	Support CVBS input	Support CVBS input
	4-ch, RCA	
Two-way Audio Input	1-ch, RCA	
Read More		
Price: KSh10,000.00 KSh12,000.00 Excl VAT		

NVR Recorders for CCTV systems are available in 9, 16 and 32 channels for IP CCTV Security Cameras monitoring and recording.

NVR301-08X-P8 8 CHANNEL 1 HDD NVR

Model	NVR301-08X-P8
Video/Audio Input	
IP Video Input	8-ch
Two-way Audio Input	1-ch, RCA
Network	
Incoming Bandwidth	80Mbps
Outgoing Bandwidth	64Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
Video/Audio Output	



HDMI/VGA Output	HDMI: 3840x2160/30Hz,1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
	VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
Recording Resolution	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Audio Output	1-ch, RCA
Synchronous Playback	8-ch
Corridor Mode Screen	3/4/5/7/9
Decoding	
Decoding format	Ultra 265/H.265/H.264
Liveview/Playback	4K/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	2 x 4k@30, 3 x 5MP@30, 4 x 4MP@30, 5 x 3MP@30,8 x 1080p@30
Hard Disk	
SATA	1 SATA interface
Capacity	up to 6TB for each disk
External Interface	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 1 x USB2.0,1 x USB3.0
PoE	
Interface	8 RJ45 10M/100M self-adaptive Ethernet Interface
Max Power	Max 30W for single port Max 75W in total
Supported Standard	IEEE 802.3at, IEEE 802.3af
General	
Power Supply	52V DC Power Consumption: ≤8 W (without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH (non-condensing)
Dimensions (W×D×H)	260mm × 240mm × 47mm (10.2"×9.4"×1.9 ")

Weight (without HDD) 1kg (2.20 lb)

[Read More](#)

Price: ~~KSh13,000.00~~ KSh15,000.00 Excl VAT

FOSCAM FN3109H 9CH NVR - NETWORK VIDEO RECORDER



- 9 channels HD IP Camera access
- H.264 Main Profile video compression
- Supports HDMI and VGA local display
- 4-ch Video Synchronous Playback
- Compatible with Foscam HD and MJPEG cameras
- Supports ONVIF protocol
- Supports USB External storage (Flashdisk,HDD)

[Read More](#)

Price: ~~KSh9,999.00~~ KSh15,999.00 Excl VAT