



OUTDOOR CCTV CAMERAS

WiFi and PoE CCTV Cameras for outdoor use in home and business including bullet and PTZ dome cameras. Buy online today with 1-year guarantee and technical support



Our Wi-Fi security cameras connect to your home wireless network in minutes and record to an microSD card. With App access with motion detection alerts

WIFI 4 CH NVR KIT - 2MP CAMERAS- 12.5 INCH SCREEN - 1TB HARD-DISK

- 4 WiFi Cameras
- 12.5 Screen NVR
- 1TB Hard-disk

[Read More](#)

Price: ~~KSh39,999.00~~ KSh44,999.00 Excl VAT

WiFi and PoE CCTV Cameras for outdoor use in home and business including bullet and PTZ dome cameras. Buy online today with 1-year guarantee and technical support

UNIVIEW IPC325LR3 5MP VANDAL-RESISTANT NETWORK IR FIXED DOME CAMERA

	IPC325LR3-VSPF28-D		IPC325LR3-VSPF40-D		
Camera					
Sensor	1/2.7", 5.0 megapixel, progressive scan, CMOS				
Lens	2.8mm@F2.0		4.0mm@F2.0		
	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
DORI Distance	2.8	42	16.8	8.4	4.2
	4.0	60	24	12	6
Angle of View (H)	105.3°		79.7°		
Angle of View (V)	69.5°		51.8°		
Angle of View (O)	136.9°		98.0°		
Adjustment angle	Pan: 0° ~ 360°		Tilt: 0° ~ 75°		
Shutter	Auto/Manual, 1 ~ 1/100000s				
Minimum Illumination	Colour: 0.01Lux (F2.0, AGC ON) 0Lux with IR				
Day/Night	IR-cut filter with auto switch (ICR)				
Digital noise reduction	2D/3D DNR				
S/N	>52dB				
IR Range	Up to 30m (98ft) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	DWDR				
Video					
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile				



Frame Rate	Main Stream: 5MP (2592*1944), Max 20fps; Sub Stream: 720P (1280*720), Max 20fps
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°
Dewarping	NA
HLC	Supported
BLC	Supported
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Compatible Integration	ONVIF (Profile S, Profile T), API
Client	EZStation EZView EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	
Network	10M/100M Base-TX Ethernet
Certifications	
	CE: EN 60950-1
Certifications	UL: UL60950-1
	FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 4W

Dimensions (Ø x H)	Φ109 x 81mm (Ø4.3" x 3.2")
Net Weight	0.45kg (0.99lb)
Material	Metal + Plastic
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Ingress Protection	IP67
Vandal Resistant	IK10

[Read More](#)

Price: ~~KSh8,000.00~~ KSh9,000.00 Excl VAT



Our PoE Surveillance Cameras save on hardware costs and installation time by delivering both power and data over a single Ethernet cable

UNIVIEW IPC2124LR3 4MP MINI FIXED BULLET NETWORK CAMERA

	IPC2124LR3-PF40M-D		IPC2124LR3-PF60M-D		
Camera					
Sensor	1/3", 4.0 megapixel, progressive scan, CMOS				
Lens	4.0mm@F2.0		6.0mm@F2.0		
	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
DORI Distance	4.0	90	36	18	9
	6.0	135	54	27	13.5
Angle of View (H)	78.9°		49.9°		
Angle of View (V)	39.6°		27.0°		
Angle of View (O)	97.0°		57.7°		
Adjustment angle	Pan: 0° ~ 360° Tilt: 0° ~ 90°			Rotate: 0° ~ 360°	
Shutter	Auto/Manual, 1 ~ 1/100000s				

Minimum Illumination	Colour: 0.03Lux (F2.0, AGC ON) 0Lux with IR on
Digital noise reduction	2D/3D DNR
Day/Night	IR-cut filter with auto switch (ICR)
S/N	>52dB
IR Range	Up to 30m (98ft) IR range
Wavelength	850nm
IR On/Off Control	Auto/Manual
Defog	Digital Defog
WDR	DWDR
Video	
Video Compression	Ultra 265, H.265, H.264, MJPEG
H.264 code profile	Baseline profile, Main Profile
Frame Rate	Main Stream: 4MP (2592*1520), Max 20fps; Sub Stream: 720P (1280*720), Max 20fps; Third Stream: D1 (720*576), Max 20fps
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
Privacy Mask	Up to 4 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°
Dewarping	NA
HLC	Supported
BLC	Supported
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Compatible Integration	ONVIF (Profile S, Profile T), API
Client	EZStation EZView EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chrome 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	

Network	10/100M Base-TX Ethernet
Certifications	CE: EN 60950-1
Certifications	UL: UL60950-1
Certifications	FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
	Power consumption: Max 5W
Dimensions (L × W × H)	167.3 × 62.9 × 62.7mm (6.6" × 2.5" × 2.5")
Net Weight	0.45kg (0.99lb)
Material	Metal
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Surge Protection	2KV
Ingress Protection	IP67
Reset Button	Supported

[Read More](#)

Price: ~~KSh7,000.00~~ ~~KSh8,000.00~~ Excl VAT

Our PoE Surveillance Cameras save on hardware costs and installation time by delivering both power and data over a single Ethernet cable

UNIVIEW IPC322LR3 2MP VANDAL-RESISTANT NETWORK IR FIXED DOME CAMERA

- IP camera
- Easy range
- 1/2.7" Progressive Scan CMOS
- 2 Megapixel (1920x1080)
- 2.8 mm Lens
- 0 Lux - IR Range 30 m
- Compression Ultra265/H.265/H.264
- RJ-45 10/100 BaseT
- PoE IEEE802.3af
- Weatherproof IP67
- Vandal proof IK10
- IR Cut
- WEB, CMS, Smartphone and NVR interface
- ONVIF Compatible



[Read More](#)

Price: ~~KSh5,000.00~~ KSh5,900.00 Excl VAT



Our PoE Surveillance Cameras save on hardware costs and installation time by delivering both power and data over a single Ethernet cable

UNIVIEW IPC2122LR3 2MP MINIFIXED BULLET NETWORK CAMERA

	IPC2122LR3-PF40M-D		IPC2122LR3-PF60M-D		
Camera					
Sensor	1/2.7", 2.0 megapixel, progressive scan, CMOS				
Lens	4.0mm@F2.0		6.0mm@F2.0		
	Lens (mm)	Detect (m)	Observe (m)	Recognize (m)	Identify (m)
DORI					
Distance	4.0	66.7	26.7	13.3	6.7
	6.0	90	36	18	9
Angle of View (H)	86.5°		55.4°		
Angle of View (V)	44.1°		30.2°		
Angle of View (O)	106.4°		68.1°		
Adjustment angle	Pan: 0° ~ 360° Tilt: 0° ~ 90°		Rotate: 0° ~ 360°		
Shutter	Auto/Manual, 1 ~ 1/100000s				
Minimum Illumination	Colour: 0.02Lux (F2.0, AGC ON) 0Lux with IR on				
Digital noise reduction	2D/3D DNR				
Day/Night	IR-cut filter with auto switch (ICR)				
S/N	>52dB				
IR Range	Up to 30m (98ft) IR range				
Wavelength	850nm				
IR On/Off Control	Auto/Manual				
Defog	Digital Defog				
WDR	DWDR				
Video					
Video Compression	Ultra 265, H.265, H.264, MJPEG				
H.264 code profile	Baseline profile, Main Profile				

	Main Stream: 1080P (1920*1080), Max 30fps; Sub Stream: 720P (1280*720), Max 30fps; Third Stream: CIF (352*288), Max 30fps
Frame Rate	
Video Bit Rate	128 Kbps~16 Mbps
OSD	Up to 4 OSDs
Privacy Mask	Up to 8 areas
ROI	Up to 2 areas
Motion Detection	Up to 4 areas
Image	
White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital noise reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Vertical/Horizontal/180°
Dewarping	Supported
HLC	Supported
BLC	Supported
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, SSL, QoS
Compatible Integration	ONVIF (Profile S, Profile T), API
Client	EZStation EZView EZLive
Web Browser	Plug-in required live view: IE9+, Chrome 41 and below, Firefox 52 and below Plug-in free live view: Chorme 57.0+, Firefox 58.0+, Edge 16+, Safari 11+
Interface	
Network	10/100M Base-TX Ethernet
Certifications	
Certifications	CE: EN 60950-1 UL: UL60950-1 FCC: FCC Part 15
General	
Power	DC 12V±25%, PoE (IEEE 802.3af) Power consumption: Max 4.5W
Dimensions (L × W × H)	167.3 × 62.9 × 62.7mm (6.6" × 2.5" × 2.5")
Net Weight	0.45kg (0.99lb)
Material	Metal
Working Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)
Storage Environment	-30°C ~ 60°C (-22°F ~ 140°F), Humidity: ≤95% RH (non-condensing)

Surge Protection	2KV
Ingress Protection	IP67
Reset Button	Supported

[Read More](#)

Price: ~~KSh5,000.00~~ ~~KSh6,000.00~~ Excl VAT

Our Wi-Fi security cameras connect to your home wireless network in minutes and record to an microSD card. With App access with motion detection alerts

WIFI 2MP 1080P 7W SOLAR CAMERA WITH AUDIO - WEATHERPROOF

- 2mp and 1080p full HD
- Support PIR human infrared detection
- Low-consumption
- Wire-free
- Audio in and audio out.

[Read More](#)

Price: ~~KSh9,999.00~~ ~~KSh10,999.00~~ Excl VAT





FOSCAM FI9902P 1080P 2MP - BULLET WI-FI CAMERA - SD CARD RECORDING

- 1080p video resolution at 25 frames per second, powered by a smart chipset
- Remote viewing and recording from anywhere, anytime
- Intelligent real-time push alerts with AI human detection
- Works with Alexa - View camera with voice control
- Wide viewing angle: Horizontal 89°, Diagonal 105°
- 6x Digital Zoom
- Night vision range up to 20 metres (66ft)
- Multiple storage methods including an external access SD slot

[Read More](#)

Price: ~~KSh6,999.00~~ ~~KSh9,999.00~~ Excl VAT

FOSCAM FI9828P WIRELESS IP OUTDOOR PTZ CAMERA

- 1.3 Megapixel HD IP Camera
- Waterproof
- H.264 video kompression and Mjpeg-stream
- Day/Night mode
- IR LEDs On/Off manually and automatically
- Nightvision up to 20 m
- Angle 70 maximum (slewing of 355 horizontal, slewing of 90 vertical)
- 2 way audio support
- Motion control via E-Mail and FTP
- Free DDNS-Service
- Minimum light intensity 0 Lux
- Power consumption

[Read More](#)

Price: ~~KSh15,999.00~~ ~~KSh19,999.00~~ Excl VAT

